



Pictured with two 25mm tape rolls.
Will accommodate up to one 50mm roll.

Best practice is grounding via supplied ground cord. Attach cord to snap on chassis and to common ground point. If grounded via placing on a grounded ESD work surface, resistance to ground (Rg) should be periodically tested $<1 \times 10E9$ ohms.

“Tools intended for use within the EPA [ESD protected area] shall, as far as is practicable, be so constructed that they do not generate or hold an electrostatic charge

All tools and machinery, for example electrical, mechanical or pneumatic, shall be so constructed that any non-insulating part of the tool or machine which may touch an ESDS [ESD sensitive items] shall be at EPA ground potential.” [EN 61340-5-1 clause 5.2.10 Tools, machinery, dispensers and test equipment]

50mm wide ESD Tape Dispenser



- **Use with Wescorp and other brand antistatic tapes**
Can be used with standard 76mm core tapes.
- **Groundable Housing and Hardware**
Components of ESD tape dispenser can be grounded with ground cord (or through work surface*) to be used in ESD Protected Area
- **Stainless Steel Construction**
Minimizes foreign objects debris, corrosion, and other contamination when used in clean or sensitive areas. Simplifies cleaning.
- **Two Separate Spools Turn Independently**
Holds one 50mm wide roll of tape or two rolls of tape that are 25mm or less widths, depending on needs.
- **Heavy Weighted Design**
Extra weight allows for one-handed use; dispenser will not slide on most surfaces.
- **Grounding Jack**
For operator personnel grounding with wrist strap or other grounding requirements
- **Made in America**



Made in Britain



Made in America

ESD Tape Dispenser, 50mm

VERMASON
UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK
PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

**DRAWING
NUMBER**
242256

DATE:
February
2009

Vermason